



Ezymix 420 – Adobe Fine (white) Technical Data Sheet

Product description

EZYMIX 420 Adobe Fine is a Graded Sand, Aggregate, White Cement, Lime Product and additives, dry mixed product for Trade use.

Product Information

EZYMIX 420 Adobe Fine is designed as a textural finishing coat to provide an undulating Adobe Finish Texture over cement based Leveling and/or intermediate coats.

EZYMIX 420 can achieve low-medium defined undulations for Adobe textures.

Min. Applied Thickness

3mm

Max. Applied Thickness

8mm



Yield Information*

Fresh Mortar Volume (V) (mixed with water)	560 litres of material per Tonne
Fresh Mortar Weight (mixed with water)	1.50 Kg per litre
Applied to Wall	4m ² per 25kg bag @ 3-5mm thickness (approx.)
<p>Figures stated on TDS are given as a guide only. As this material is designed to give an undulating finish, yield volumes will vary depending on application thickness and technique.</p>	

Mixing Information

Dependant on use and only as a guide EZYMIX 420 Adobe Fine requires approx. 20% water added or as required to achieve the required workable consistency. Material to be mixed by machine or with suitable drill and paddle method.

EZYMIX 420 Adobe Fine can be pump applied.

1 x 25kg bag = 5 litres of water

Note:

Water added must be clean potable water.

Water temperature may alter the workable time for this product.

Storage

The material must be kept dry and sealed, stored off the floor in a manner where moisture cannot come into contact with the bag or its contents.

This Product has a shelf life of **9 months** after date of manufacture if stored as detailed above.

Quality Control

EZYMIX – 420 Adobe Fine is manufactured to specification in New Zealand by Nu-Age Plaster Ltd utilising automated weighing and batching equipment in conjunction with Telarc Q Base quality control regime, the manufacture of this product is guaranteed.

If unsatisfied with any EZYMIX Materials please contact.



*Yield Information given as a guide only.