

EM815 TILT PANEL PATCH

General Product Description

EZYMIX EM815 Tilt Panel Patch is a cement based, sandable patching plaster for fixing imperfections and minor voids over tilt slab substrates.



Product Info and Limitations

EM815 Tilt Panel Patch should be mixed to a 'toothpaste' consistency and applied either in single or multiple thin layers to uncoated concrete substrates

Once dry, EM815 can be sanded using a fine grit sandpaper to give a finely ground surface masking imperfections in the tilt slab face.

As a guide EM815 Tilt Panel Patch requires approx. 30-35% water added or as required to achieve the required workable consistency.

Material to be mixed by machine or with suitable drill and paddle method.

1 x 20kg bag = 6 litres of water

Min. Applied Thickness – 0.2mm

Max. Applied Thickness – 2mm

Product Yield

Fresh Mortar Volume	19 litres mixed material per 20kg bag
m2 coverage	approx. 10-12m2 @ 1mm thickness

Figures are based on a flat substrate with no deviations in substrate or material thickness.

EM815 Tilt Panel Patch is supplied in 20kg bags, 50 bags per T.



Quality Construction Solutions

Application Information

If minor voids are present, apply EM815 using a trowel or broadknife to fill these voids first then allow to dry completely.

Hand sand the filled areas until they are flush with the face of the tilt slab.

If additional filling or recoating is required trowel another thin layer over the area and allow to dry before sanding back to a desired level.

EM815 is coloured light grey, patched areas may be evident dependant on the colour of the original tilt slab.

If required the entire tilt slab may be 'skimmed' to ensure uniform colour or alternatively painted.

Product Guarantee

EZYMIX products are Guaranteed to be manufactured to consistent specification or replacement material will be supplied.

EZYMIX cannot be held liable for the application of the material outside the specifications stated in this and other associated Technical Literature, for application which does not meet current Trade Practices and any application prior to consultation on use with EZYMIX staff.

Additional Info

EZYMIX products loves to be mixed using automated on-site mixing equipment. The D-20 mixer adds the perfect amount of water and mixing time to ensure consistent mixes time after time. If you would like information regarding to the D-20 mixing machine please contact EZYMIX.

Handling and Storage

The material must be kept dry and sealed, stored off the floor in a manner where moisture cannot come into contact with the bag or its contents.

This Product has a shelf life of 6 months after date of manufacture if stored as detailed above. Manufactured dates are clearly labelled on each bag.

Please refer to product Safety Data Sheet prior to use and always wear Protective Personal Equipment.

EM815 TTP TDS – V5 Expires April 2017 Pg 1 of 2