



Ezymix 430 – Scratchputz Technical Data Sheet

Product description

EZYMIX 430 Scratchputz is a Graded Sand, Aggregate, White Cement, High Grade Lime Product and additives, dry mixed product for Trade use.

Product Information

EZYMIX 430 Scratchputz is designed to provide 'highly buildable' and heavy undulating Adobe Finish Texture over cement based Leveling and/or intermediate coats.

EZYMIX 430 Scratchputz can achieve more defined undulations and textures than a conventional Adobe Finishing Plaster.

Min. Applied Thickness*	8mm
Max. Applied Thickness*	15mm

* Minimum and Maximum applied thicknesses stated above refer to a single coat application of EZYMIX 430.



Yield Information*

Fresh Mortar Volume (V) (mixed with water)	15.5 litres of material per 25kg bag
Fresh Mortar Weight (mixed with water)	1.52 Kg per litre
Applied to Wall	2m ² per 25kg bag @ 8mm thickness (approx.)

Figures stated on TDS are given as a guide only.
As this material is designed to give an undulating finish, yield volumes will vary depending on application thickness and technique.

Mixing Information

Dependant on use and only as a guide EZYMIX 430 Scratchputz requires approx. 20% water added or as required to achieve the required workable consistency. Material to be mixed by machine or with suitable drill and paddle method.

EZYMIX 430 Scratchputz can be pump applied.
1 x 25kg bag = 5 litres of water

Note:

Water added must be clean potable water.
Water temperature may alter the workable time for this product.

Storage

The material must be kept dry and sealed, stored off the floor in a manner where moisture cannot come into contact with the bag or its contents.

This Product has a shelf life of **9 months** after date of manufacture if stored as detailed above.

Quality Control

EZYMIX 430 Scratchputz is manufactured to specification in New Zealand by Nu-Age Plaster Ltd utilising automated weighing and batching equipment in conjunction with Telarc Q Base quality control regime, the manufacture of this product is guaranteed.

If unsatisfied with any EZYMIX Materials please contact.

*Yield Information given as a guide only.