

EM270 MULTI

General Product Description

EZYMIX – MULTI 270 is a highly adhesive render containing graded sand, white cement, high grade lime supplement and additive, dry mixed product for use over Porous and non-porous substrates;

- Previously Painted surfaces,
- Masonry substrates
- Fibre cement sheet and EPS



Product Info and Limitations

Designed as a highly adhesive Plaster this materials scope consists of;

- The adhering of EPS or keyed XPS to Solid Substrates
- Utilised as a key coat over smooth surface such as painted or smooth substrates.
- Can be applied with glass fibre mesh as a mesh coat or reinforcement in difficult areas.
- Mixed as a slurry, applied to PVC componentary to be plastered or coated.

Min. Applied Thickness – 1mm
Max. Applied Thickness – 8mm

EM270 MULTI requires approx. 20% water added or as required to achieve the required workable consistency. Material to be mixed by machine or with suitable drill and paddle method.

1 x 25kg bag = 5 litres of water

Product Yield

Fresh Mortar Volume	14.3 litres mixed material per 25kg bag
m2 coverage	approx. 3m2 @ 5mm thickness per 25kg bag

Figures are based on a flat substrate with no deviations in substrate or material thickness.

EM270 MULTI is supplied in 25kg bags, 40 bags per T.



Quality Construction Solutions

Application Information

As an **Adhesion Plaster**, apply the material direct to the back face of the EPS or keyed XPS using a specialised application machine or 10mm notched trowel. See associated documentation in relation to laying instructions.

As a **Key Coat**, apply the material using a standard or notched trowel to the painted or smooth surface. Do not overcoat until completely dry.

As a **Mesh Coat**, Apply the material in the usual fashion directly to the substrate and apply the glass fibre mesh to the wet surface.

Trowel in the mesh until covered with material.

Mixed as a **Slurry**, Mix using approx 40% water and brush onto PVC componentry. Do not overcoat until completely dry.

Product Guarantee

EZYMIX products are Guaranteed to be manufactured to consistent specification or replacement material will be supplied.

EZYMIX cannot be held liable for the application of the material outside the specifications stated in this and other associated Technical Literature, for application which does not meet current Trade Practices and any application prior to consultation on use with EZYMIX staff.

Additional Info

EZYMIX products loves to be mixed using automated on-site mixing equipment. The D-20 mixer adds the perfect amount of water and mixing time to ensure consistent mixes time after time. If you would like information regarding to the D-20 mixing machine please contact EZYMIX.

Handling and Storage

The material must be kept dry and sealed, stored off the floor in a manner where moisture cannot come into contact with the bag or its contents.

This Product has a shelf life of 12 months after date of manufacture if stored as detailed above. Manufactured dates are clearly labelled on each bag.

Please refer to product Safety Data Sheet prior to use and always wear Protective Personal Equipment.

EM270 M TDS – V5 Expires April 2017 Pg 1 of 2