

ADHESIVE (AD) SEALING TAPE

Reinforced Self-adhesive tape, for
sealing under tiles in wet rooms

Properties

Fleece coated, permanently elastic butyl sealing tape with a high adhesive strength and tear resistance. The fleece coating allows an excellent bond with neutral cure silicone and the EM240 (IWM) Internal Waterproofing Membrane.

Field of application

Used to seal the floor to wall junction in wet areas, not to be cut and used to form an internal or external corner.

The AD Sealing Tape & AD Internal / External Corners are covered with 2 topcoats of the EM240 IWM.

Technical specifications:

Thickness:	0.60 mm
Width:	100 mm
Working temperature:	+5°C

AD Sealing Tape Installation

Sealing tapes can only be applied over clean & dry substrates that have been primed with EM230 FG Tile Primer. All internal/external floor to wall junctions and vertical internal/external corners must have sealing tapes installed prior to the application of EM240 (IWM) Internal Waterproofing Membrane.

Install internal & external corners first.

Remove the first half of the backside liner of the self-adhesive corner and press onto floor then remove the second half of the backside liner and press onto the wall.

Roll or press into the internal point of the junction to ensure correct bond then do the same for the rest of the tape including edges.

When cutting the AD Butyl Sealing tape between internal & external corners there must be a minimum 50mm overlap onto the preformed corners.

Cut the AD Butyl Sealing tape to length, remove the first section of the backside liner and press onto the floor, remove the remaining backside liner and press into place. Repeat this process for the wall side and then roll or press into the internal point of the junction to ensure correct bond then do the same for the rest of the tape including edges.



Consumption

When calculating consumption, allow for a minimum tape overlap of 50mm.

Cleaning of tools and equipment

Tools and soiled areas should be cleaned immediately after use with water.

Storage

Can be stored in the original sealed packaging for up to 24 months in a cool, dry environment.

Logistics

20 m roll
4 rolls / carton
42 cartons / pallet

Safety information

This product is not hazardous as defined in the Hazardous Substances Code.

Disposal

May be disposed of as construction waste.