

NON ADHESIVE (NA) EXTERNAL CORNER

Fleece coated elastic shape for durable sealing of External corners in combination with sealing systems under tiles.



Properties

The NA External Corner is a watertight, durable elastic 1 piece corner. The pre-formed pieces are made from NBR-Rubber with both sides polyester non-woven. This material creates an excellent bonding with the EM240 IWM when used under tiles extending over the entire surface of the corner.

Field of application

Used to seal external corner floor to wall junction in wet areas, installed with EM240 (IWM) Internal Waterproofing Membrane.

Technical specifications:

Thickness	0.60 mm
Temperature resistance	-20°C to +90°C

NA Internal Corner Installation

Sealing tapes can only be applied over clean & dry substrates that have been primed with EM230 FG Tile Primer. All internal/external floor to wall junctions and vertical internal/external corners must have sealing tapes installed prior to the application of EM240 (IWM) Internal Waterproofing Membrane.

Using a small roller, brush or trowel apply an even coat of EM240 IWM to the wall/floor internal corner junction.

Press the NA External Corner into the fresh EM240 IWM, carefully remove excess EM240 IWM to minimize creasing & eliminate ridges. This step is replicated for all internal and external corners.

Once all NA Sealing Tapes have been installed apply an even coat of EM240 IWM overtop of all the sealing tapes including the internal & external corners. Carefully remove any excess edges / ridges.

Consumption

When calculating consumption, allow for a tape overlap of a minimum of 50mm.

Cleaning of tools and equipment

Tools and soiled areas should be cleaned immediately after use with water.

Storage

Can be stored in the original sealed packaging for up to 24 months in a cool, dry environment.

Logistics

10 pieces/ carton

Safety information

This product is not hazardous as defined in the Hazardous Substances Code.

Disposal

May be disposed of as construction waste.