

NON ADHESIVE (NA) SEALING TAPE

Fleece coated NBR rubber elastic sealing tape with good lateral extension

Properties

Both sides are a non-woven coated NBR rubber elastic sealing tape with low textile content. The tape exhibits excellent recovery characteristics and is fully compatible with neutral cure silicone & EM240 (IWM) Internal Waterproofing Membrane.

Field of application

Used to seal the floor to wall junction in wet areas, not to be cut and used to form an internal or external corner.

Technical specifications:

Thickness	0.60 mm
Width	120 mm
Weight	50 g/m
Equivalent air layer thickness sd:	5 m
Water pressure resistance	leakproof at 3 bar
Elongation, lateral direction	250 %
Elongation, lengthwise direction	50 %
Temperature resistance	-20°C to +90°C

NA Sealing Tape Installation

Sealing tapes can only be applied over clean & dry substrates that have been primed with EM230 FG Tile Primer. All internal/external floor to wall junctions and vertical internal/external corners must have sealing tapes installed prior to the application of EM240 (IWM) Internal Waterproofing Membrane.

Install internal & external corners first.

When cutting the NA Sealing tape between internal & external corners there must be a minimum 50mm overlap onto the preformed corners.

Using a small roller, brush or trowel apply an even coat of EM240 IWM to the wall/floor internal junction.

Press the NA Sealing Tape into the fresh EM240 IWM, carefully remove excess EM240 IWM to minimize creasing & eliminate ridges.

Repeat the above process to all internal junctions.

Once all NA Sealing Tapes have been installed apply an even coat of EM240 IWM overtop of all the sealing tapes including the internal & external corners. Carefully remove any excess edges / ridges.



Consumption

When calculating consumption, allow for a tape overlap of a minimum of 50mm.

Cleaning of tools and equipment

Tools and soiled areas should be cleaned immediately after use with water.

Storage

Can be stored in the original sealed packaging for up to 24 months in a cool, dry environment.

Logistics

50 m roll
1 roll / carton
144 cartons / pallet

Safety information

This product is not hazardous as defined in the Hazardous Substances Code.

Disposal

May be disposed of as construction waste.