

NON ADHESIVE (NA) WALL SLEEVE

Fleece-coated wall sleeve for a permanent sealing of pipe passages in combination with sealing systems under tiles.

Properties

The NA Wall Sleeve is watertight & permanently sealing. The sleeve is made of polyethylene foil reinforced with on both sides with non-woven and a flexible zone based on NBR rubber in the middle. This material basis causes an excellent bonding with the EM240 (IWM) Internal Waterproofing Membrane used under tiles extending over the entire surface of the sleeve.

Field of application

The NA Wall Sleeve is suitable as permanently watertight sealing on wall areas for pipe passages of shower and bathtub water fittings under ceramic coverings. The sleeve is completely embedded into the EM240 IWM.

Technical specifications:

Total measurements	120 x 120 mm
	150 x 150 mm
	200 x 200 mm
	250 x 250 mm


Flexible zone based on NBR rubber

NA Wall Sleeve Installation

Using a small roller, trowel or brush apply an even layer of EM240 IWM to an area slightly larger than the size of the NA Wall Sleeve.

The NA Wall Sleeve is put over the pipe and pushed evenly into the wet EM240 IWM. Carefully remove any excess EM240 IWM to minimize creasing & eliminate ridges.

Once all NA Sealing Tapes have been installed apply an even coat of EM240 IWM overtop of all the sealing tapes including the internal & external corners, wall & floor sleeves. Carefully remove any excess edges / ridges.



Cleaning of tools and equipment

Tools and soiled areas should be cleaned immediately after use with water.

Storage

Can be stored in the original sealed packaging for up to 24 months in a cool, dry environment.

Logistics

20 pieces/ carton

Safety information

This product is not hazardous as defined in the Hazardous Substances Code.

Disposal

May be disposed of as construction waste.